



SAFETY DATA SHEET

1. Identification

Product identifier: GEL VANDAL MARK REMOVER Canadian Importer
Advantage Maintenance Products Ltd.
105 Scott Ave
Paris, ON N3L 3E7
(519) 442-7881

Other means of identification
SDS number: RE1000010419

Recommended restrictions
Recommended use: Cleaner.
Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Company Name: CLAIRES MANUFACTURING COMPANY
Address: 1000 Integram Dr
Pacific, MO 63069
Telephone: 1-630-543-7600

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Specific Target Organ Toxicity -
Single Exposure Category 3¹
Specific Target Organ Toxicity -
Repeated Exposure Category 2
Aspiration Hazard Category 1

Target Organs

1.Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic
environment Category 3

Label Elements

Hazard Symbol:



Signal Word:

Danger



Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Benzene, methyl-		108-88-3	10 - 30%
Propane		74-98-6	5 - 10%
2-Propanone		67-64-1	5 - 10%
Butane		106-97-8	5 - 10%
Ethanol, 2-butoxy-		111-76-2	1 - 5%
Ethanol, 2-(2-butoxyethoxy)-		112-34-5	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



4. First-aid measures

Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	No data available.
-------------------	--------------------

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.
--	---

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
---	---



Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Benzene, methyl-	TWA	50 ppm 188 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Benzene, methyl-	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene, methyl-	8 HR ACL	50 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	60 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Benzene, methyl-	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Benzene, methyl-	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Benzene, methyl-	TWA	20 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Benzene, methyl-	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Propane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Propane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
2-Propanone	STEL	750 ppm 1,800 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)



2-Propanone	STEL	500 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Propanone	TWA	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
	STEL	500 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
	TWA	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Propanone	TWA	250 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2015)
2-Propanone	8 HR ACL	500 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	STEL	500 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2015)
2-Propanone	STEL	1,000 ppm 2,380 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	500 ppm 1,200 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	500 ppm 1,190 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	15 MIN ACL	750 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
2-Propanone	TWA	250 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	500 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
Butane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Butane	STEL	750 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
	TWA	600 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
Butane	TWA	800 ppm 1,900 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Butane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Butane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended (03 2018)
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethanol, 2-butoxy-	TWA	20 ppm 97 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Ethanol, 2-butoxy-	15 MIN ACL	30 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	20 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Ethanol, 2-butoxy-	TWA	20 ppm 97 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2013)
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)



Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended (03 2013)
Sodium hydroxide (Na(OH))	CEILING		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Sodium hydroxide (Na(OH))	CEILING		2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Sodium hydroxide (Na(OH))	CEV		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Sodium hydroxide (Na(OH))	CEILING		2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Sodium hydroxide (Na(OH))	CEILING		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Morpholine	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Morpholine	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Morpholine	TWA	20 ppm	71 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Morpholine	TWA	20 ppm	71 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Morpholine	8 HR ACL	20 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	30 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Morpholine	TWA	20 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Morpholine	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Crystalline Silica - Respirable fraction.	8 HR ACL		0.05 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Crystalline Silica - Respirable particles.	TWA		0.025 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear safety glasses with side shields (or goggles).



Skin Protection	
Hand Protection:	No data available.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	Estimated 9.5 %(V)
Flammability limit - lower (%):	Estimated 1.9 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	3,102 - 4,481 hPa (20 °C) 6,550 - 7,928 hPa (54 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
--------------------	--------------------



Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 22,503.78 mg/kg
Dermal	
Product:	ATEmix: 17,029.26 mg/kg
Inhalation	
Product:	ATEmix: 273.29 mg/l ATEmix : 63.22 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Benzene, methyl-

LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target Organ(s): Liver, Kidney) Oral Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation Experimental result, Key study



Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
2-Propanone	NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study
Butane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Benzene, methyl-	in vivo (Rabbit): Irritating Experimental result, Key study
2-Propanone	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Ethanol, 2-butoxy-	in vivo (Rabbit): Irritating Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	in vivo (Rabbit): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Benzene, methyl-	Rabbit, 24 - 72 hrs: Not irritating
2-Propanone	Irritating. Rabbit, 24 hrs: Minimum grade of severe eye irritant
Ethanol, 2-butoxy-	Rabbit, 24 - 72 hrs: Irritating
Ethanol, 2-(2-butoxyethoxy)-	Rabbit, 24 - 72 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Benzene, methyl-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
2-Propanone	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-butoxy-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-(2-butoxyethoxy)-	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

ACGIH Carcinogen List:
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specified substance(s):
Benzene, methyl- Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure
Product: Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure
Product: Category 2

Target Organs
Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard
Product: No data available.

Specified substance(s):
Benzene, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Benzene, methyl-	LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
2-Propanone	LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study



Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)- LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality
LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Ethanol, 2-butoxy- EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)- LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study
LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Benzene, methyl- LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study
NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Ethanol, 2-butoxy- EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study
EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Benzene, methyl- 100 % (14 d) Detected in water. Experimental result, Weight of Evidence study
86 % Detected in water. Experimental result, Weight of Evidence study



Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
2-Propanone	90.9 % (28 d) Detected in water. Experimental result, Key study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Ethanol, 2-butoxy-	90.4 % Detected in water. Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	85 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Benzene, methyl-	Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment Experimental result, Key study
2-Propanone	Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Benzene, methyl-	No data available.
Propane	No data available.
2-Propanone	No data available.
Butane	No data available.
Ethanol, 2-butoxy-	No data available.
Ethanol, 2-(2-butoxyethoxy)-	No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.



14. Transport information

TDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	None known.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	F-D, S-U
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	None known.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	None known.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Chemical Identity

2-Propanone
Ethanol, 2-butoxy-

Export Control List (CEPA 1999, Schedule 3)

Chemical Identity

2-Propanone



National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5	Benzene, methyl- Propane 2-Propanone Butane Ethanol, 2-butoxy-
----------	--

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI	Benzene, methyl- 2-Propanone Ethanol, 2-butoxy-
------	---

Greenhouse Gases

Chemical Identity

2-Propanone

Controlled Drugs and Substances Act

CA CDSI	2-Propanone
CA CDSII	2-Propanone
CA CDSIII	2-Propanone
CA CDSIV	2-Propanone
CA CDSV	2-Propanone
CA CDSVII	2-Propanone
CA CDSVIII	2-Propanone

Precursor Control Regulations

Chemical Identity

Benzene, methyl-
2-Propanone

International regulations

Montreal protocol

2-Propanone

Stockholm convention

2-Propanone

Rotterdam convention

2-Propanone	Organics
-------------	----------

Kyoto protocol



Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Mexico INSQ:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date:	12/07/2021
Revision Date:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.