



SAFETY DATA SHEET

1. Identification

Product identifier 19 OZ SW PENETRATING COIL CLNR LB 12PK

Other means of identification

Product code 1000010102

Recommended use cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Sprayway, Inc.
Address 1000 INTEGRAM DR
Pacific, MO 63069
United States
Telephone 1-630-628-3000
E-mail orders@spraywayinc.com
Emergency phone number Emergency - US 1-866-836-8855
Emergency - Outside US 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Health hazards Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	1 - 5
Butane		106-97-8	1 - 5
EDTA Tetrasodium Salt		64-02-8	1 - 5
Propane		74-98-6	1 - 5
Lemon Terpenes		68917-33-9	0.1 - 1
Sodium Nitrite		7632-00-0	0.1 - 1
Terpene Hydrocarbons		68956-56-9	0.1 - 1
Other components below reportable levels			60 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid breathing gas. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	TWA	800 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Aerosol.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.989 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
Inhalation	Rat	> 2000 mg/kg, 24 Hours
	Rabbit	400 ppm, 7 Hours
		450 ppm, 4 Hours
	Rat	
Oral		
LD100	Rabbit	695 mg/kg
	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
LD50	Rat	1746 mg/kg

Components	Species	Test Results
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
EDTA Tetrasodium Salt (CAS 64-02-8)		
<u>Acute</u>		
Oral		
LD50	Rat	1658 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Sodium Nitrite (CAS 7632-00-0)		
<u>Acute</u>		
Oral		
LD50	Rat	180 mg/kg
Terpene Hydrocarbons (CAS 68956-56-9)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

2-Butoxyethanol (CAS 111-76-2) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

2-Butoxyethanol (CAS 111-76-2) A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Manitoba OELs: carcinogenicity

2-BUTOXYETHANOL (EGBE) (CAS 111-76-2) Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	May be harmful if absorbed through skin.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
EDTA Tetrasodium Salt (CAS 64-02-8)			
Aquatic			
Algae	IC50	Algae	1.01 mg/L, 72 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours
Sodium Nitrite (CAS 7632-00-0)			
Aquatic			
Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis)	16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.15 - 0.25 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol	0.83
Butane	2.89
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-

Packing group Not applicable.

Environmental hazards D

Special precautions for user Not available.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Environmental hazards No.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 03-12-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names